

Model: 660MRL 230V Thermally enhanced optical smoke alarm

The 660MRL is a mains powered thermally enhanced optical smoke alarm with a rechargeable lithium battery back-up. Thermally enhanced optical technology combines very latest in optical sensing with a thermal enhancement, providing fast reaction to both slow smouldering and fast flaming fires in a single alarm.



Product features:

- 230V mains powered smoke alarm
- Rechargeable lithium battery back-up
- Thermally enhanced optical technology reduces nuisance alarms
- Test and alarm pause button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke and heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS EN 14604: 2005

| | |
|------------------------|--|
| Model number | 660MRL |
| Description | 230V smoke with rechargeable battery bk-up |
| Sensitivity | N/A |
| Alarm sound level | 85db at 3 metres |
| Battery type | Rechargeable lithium |
| Operation AC/DC | AC |
| Installation positions | Ceiling |
| Operating temperature | 5°C (40°F) to 38°C (100°F) |
| Operating humidity | 10% to 85% relative |
| Storage temperature | 5°C (40°F) to 38°C (100°F) |
| Storage humidity | 10% to 85% relative |
| Warranty | 5 years |

| | |
|---------------------------|----------------------------------|
| Dimensions - Alarm + Base | 140mm (D) x 44mm (H) |
| Unit weight - Alarm | 187g |
| Pack dimensions | 141mm (H) x 141mm (W) x 48mm (D) |
| Pack weight | TBC |
| Master pack quantity | 10 |
| Master pack dimensions | TBC |
| Master pack weight | TBC |
| Pack barcode | 5022391065302 |
| Outer barcode | 15022391065309 |
| Approvals | BS EN 14604: 2005 |