

The 790MBX is a mains powered heat alarm with 9V alkaline battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix).



Product features:

- 230V mains powered heat alarm
- 9V alkaline battery back-up
- PUSH-FIT docking base (DS700 included)
- Class A2 - Thermistor sensing technology
- Test button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke and heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS 5446-2: 2003

Model number	790MBX (1 x 690MBX + 1 x DS700 base)
Description	230V heat with alkaline battery bk-up
Technology	Thermistor
Sensitivity	N/A
Alarm sound level	85db at 3 metres
Battery type	9V PP3 Alkaline
Operation AC/DC	AC
Installation positions	Ceiling
Operating temperature	5°C (40°F) to 38°C (100°F)
Operating humidity	10% to 85% relative
Storage temperature	5°C (40°F) to 38°C (100°F)
Storage humidity	10% to 85% relative
Warranty	5 years

Dimensions - Alarm + Base	140mm (D) x 68mm (H)
Dimensions - Base	140mm (D) x 33mm (H)
Unit weight - Alarm	286g
Unit weight - Base	91g
Pack dimensions	141mm (H) x 141mm (W) x 76mm (D)
Pack weight	TBC
Master pack quantity	10
Master pack dimensions	TBC
Master pack weight	TBC
Pack barcode	5022391065333
Outer barcode	15022391065330
Approvals	BS 5446-2: 2003